

- Wall Mounting
- IP66 Protection
- Security Glazed Door
- Fully Key Lockable
- Accepts Most GDS Controllers & Auxiliary Products



Dimensions

Enclosure height 400 mm
Enclosure width 400 mm
Enclosure depth 200 mm

Door type

Glazed

Composition

1 body
1 door
1 lock
1 cable gland plate

Body type

Single piece body
Gutter-shaped front rail double sheet thickness

Number of doors

Front face: 1 door

Door opening side

Reversible (120°)

Lock type

3 mm double-bar lock (2 keys supplied)

Accessibility for operation

Front

Material

Body – Steel
Door – Steel and security glass

Finish

Epoxy-polyester powder

Colour

Grey (RAL 7035)

Standards

IEC 62208

Product certifications

CUL, GL, BV, LR, UL, DNV

Net weight

3.6 kg

Electromagnetic compatibility Electromagnetic field immunity test

Protection

IP66 IEC 60529
IK08 IEC 62262

Removable parts

1 Door by hinges



2 Cable gland plate by screws

This document is not contractual and the specification / detail may be modified at any time without prior notice.
Declaration of Conformity C1508

E: sales@gds-technologies.co.uk T: +44 (0)113 286 0166

GDS TECHNOLOGIES LTD | FUSION POINT | ASH LANE | GARFORTH | LEEDS | LS25 2GA | UK



www.gds-technologies.co.uk